



AZIENDA

L'esperienza maturata da più di 40 anni nel settore della produzione di macchine per l'industria dell'abbigliamento, ci ha permesso di diventare partner di fiducia di molte aziende italiane ed estere, offrendo anche soluzioni personalizzate. Tutti i nostri applicatori manuali e pneumatici sono costruiti in Italia, si distinguono per l'ottimo rapporto qualità prezzo e da sempre sono impiegati per l'applicazione di bottoni a pressione, rivetti, anelli e minuteria metallica nei vari settori quali:

- abbigliamento
- pelletteria
- cartotecnica
- produzione di teloni, reti
- tendaggi

COMPANY

The experience gained from more than 40 years in the production of machines for the garment industry has allowed us to become a trusted partner of many Italian and foreign companies, also offering customized solutions. All our manual and pneumatic applicators are made in Italy, they are distinguished for the excellent value for money and have always been used for the application of snap buttons, rivets, eyelet grommets and small metal parts in the various areas such as:

- clothing
- leather
- stationery items
- production of tarpaulins, nets
- curtains



Applicatori per minuteria
Applicators for snaps

◆ S50

Applicatore manuale
Manual applicator



◆ S50L

Applicatore manuale
Manual applicator



◆ G100

Applicatore a pedale
Pedal applicator



◆ TR60

Applicatore a pedale con ruote e maniglia
per un facile spostamento.
Applicator pedal with wheels and handle
for easy movement.



◆ MT10 - MT20

Applicatore pneumatico ad una testa (MT10) e a due teste (MT20) con avviamento meccanico. Disponibile nelle due versioni anche con profondità di lavoro di 16 cm (MT10/SL e MT20/SL).
Pneumatic applicator one head (MT10) and two heads (MT20) with mechanical starting. The two versions are also available with a working depth of 16 cm (MT10/SL and MT20/SL).



MT10



MT20

◆ GS/S - GS/D

Applicatore pneumatico ad una testa (GS/S) e a due teste (GS/D)
Pneumatic applicator one head (GS/S) and two heads (GS/D)



GS/S



GS/D

◆ GS/S-DC GS/D-DC

Applicatore pneumatico con cilindro a membrana da 20" o da 30" a una testa (GS/S-DC), due teste (GS/D-DC) o in versione ibrida (GS/S-1DC).
Pneumatic applicator with cylinder at membrane of 20" or of 30" one head (GS/S-DC), two heads (GS/D-DC) or in a hybrid version (GS/D-1DC)



GS/S-DC



GS/D-DC



Versione GS/D-1DC /
GS/D-1DC Version

◆ T12

Applicatore pneumatico da banco
Pneumatic bench applicator



CE

METALMECCANICA